



Flush mounting box 4M light blue: Flush mounting box 4M light blue

V71304

Flush mounting box 4M light blue

4-module flush mounting box, (Glow Wire 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various cross-
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing



Product Status

3 - Active

Minimum order quantity

6 NR

You may also be interested in










V71304.AU - Flush mounting V71324 - Antimortar cover box 4M black for flush-mount box 4M

V71634 - Flat cover 4M


V71550 - Dividing screen for flush-mount box yell




Drawings



Space view





3D View

Backside view

Technical data

- Class group: Connection material (electrotechnical)
- Class: Box/housing for built-in mounting in the wall/ceiling
- Mounting method: Flush-mounted
- Shape: Rectangular
- **Construction type**: Device connection box (round/square)
- Model: Other
- Provided with revolving ring: No
- Couplable: Yes
 Equipped with: None
 Diameter: 0 mm
 Length: 59,00 mm
 Width: 121,00 mm
 Depth: 0,00 49,80 mm
 Inner depth: 50,00 mm
- For number of electric fittings: 4
- Mounting switching equipment: Screwing
- With screws: No
- Housing feed-through by break-out opening: Yes
 Housing feed-through by seal membrane: No
- Housing feed-through by nozzle: No
- Housing feed-through by step membrane: No
- For tube diameter: 20/25 mm
- Pipe locking: No

- Pipe locking optional: No
- **Inlet from the rear**: Yes
- Number of inlets: 14
- Number of included spouts: 0
- Material: Plastic Halogen free: Yes
- **Surface protection**: Untreated
- Colour: Blue
- Degree of protection (IP): IP00
- Cover model: None
 Transparent cover: No
 Cover attachment: Screwed
- Sealable: No
- Circuit integrity: None With screening: No
- Air tight: No
- Max. conductor cross section: 0
 Number of poles of the clamp: 0
- Clamp position fixed: No Luminaire hook mounting: No
- Nozzle: None
- **Special application**: None

Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 15. CCC China (download)

- 43. UKCA mark Great Britain
- 50. Product Environm. Profile
- 96. Electrotechnical expert (download)

Packaging



Code Quantity Dim. Weight

8007352079403 1 NR 13.1x6.9x5 [cm] 38.2 [g]



Code Quantity Dim. Weight

8007352079410 6 NR 13.1x6.9x30 [cm] 238.27 [g]



Code Quantity Dim. Weight

8007352079427 96 NR 59.5x38.5x26.5 [cm] 4.595.33 [g]



Code Quantity Dim. Weight

8007352356245 2,304 NR 80x120x180 [cm] 115,000 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.