



KNX cable 2x2x0,8mm LSZH Eca 100m green: KNX cable 2x2x0,8mm LSZH Eca 100m green

01890.E

KNX cable 2x2x0,8mm LSZH Eca 100m green

KNX system cable, 2x2x0,8 mm cable, LSZH sheath, CPR Eca class, according to KNX standard, suitable for installation with I Category power supply cables (U0 = 400 V), green - 100 m reel



Product Status

3 - Active

Minimum order quantity

100 M

Technical data

- **Class group:** Cables
- **Class:** Data and communication cable
- **Diameter conductor:** 0,80 mm
- **Nominal cross section conductor:** 0,50
- **Conductor category:** Class 1 = solid
- **Number of cores:** 4
- **Stranding element:** Pairs
- **Material core insulation:** Other
- **Core identification:** Colour
- **Screen over stranding element:** None
- **Screen over stranding:** Foil
- **Material outer sheath:** Other
- **Colour outer sheath:** Green
- **Outer diameter approx.:** 6,00 mm
- **Permitted cable outer temperature during assembling/handling:** 20 - 80 °C
- **Category:** Other

Certifications

- 00. CE Marking - EU ([download](#))
- 00. CE Marking - EU ([download](#))
- 27. KNX ([download](#))
- 43. UKCA mark - Great Britain

Packaging



Code 8007352574601
Quantity 1 M
Dim. 100x0,6x0,6 [cm]
Weight 51,26 [g]



Code 8007352574618
Quantity 100 M
Dim. 27x27x11 [cm]
Weight 5,593 [g]



Code 8007352599086
Quantity 300 M
Dim. 38x34x24 [cm]
Weight 15,380 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).