



250V 16A 4-output actuator KNX: 250V 16A 4-output actuator KNX

01523.1

250V 16A 4-output actuator KNX

Actuator with 4 NO relay outputs 16 A 250 V~, programmable with control function for lights, roller shutters with slat orientation, push buttons for local control, KNX standard, installation on DIN rail (60715 TH35), occupies 4 modules size 17.5 mm

Product Status

3 - Active

Minimum order quantity

1 NR

Sheets, Manuals, Documentation


- [Multilanguage instructions sheet \(917 kb\)](#)
- [Manuale installatore \(2707 kb\)](#)
- [Manuale installatore \(2591 kb\)](#)

Product Software

- [DB_ComponentiAutomazione_KNX_01.16_20210920.zip](#)
- [DB_ComponentiAutomazione_KNX_01.19_20230331.zip](#)




Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Installation bus systems
- **Class:** Actuating drive for bus system
- **Bus system KNX:** Yes
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Radio frequent bidirectional:** No
- **Mounting method:** Other
- **With bus connection:** Yes
- **Temperature control with built-in continuous control:** No
- **Buttons for manual operation at the drive:** Yes
- **Function master/slave:** No
- **Nominal voltage:** 250 V
- **Voltage supply over bus:** No

Certifications

- 00. CE Marking - EU
- 27. KNX ([download](#))
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352644359
Quantity 1 NR
Dim. 11.7x10.8x7.1 [cm]
Weight 273 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).